

FRONIUS DATALOGGER WEB

/ Datalogger with Wi-Fi®* functionality



/ The Fronius Datalogger Web is the ideal interface between the inverter and PC, and is used for logging and monitoring PV system data. It can easily be integrated into existing networks using its Ethernet interface. This can also be done using an optional Wi-Fi* stick. Up-to-date information from systems with up to 100 inverters can be read in real time.

FRONIUS DATALOGGER WEB

TECHNICAL DATA

Storage capacity	max. 4,096 days
Supply voltage	12 V DC
Power consumption	Type 1.43 W
Degree of protection	IP 20
Dimensions	190 x 114 x 53 mm

INTERFACES

Relay output	42 V AC / 6 A 60 V DC / 400 mA 40 V DC / 1 A 30 V DC / 6 A 0.8 – 1.5 mm ² cable cross-section
External supply, terminal	12 V DC / max. 1 A, Class 2 0.13 – 1.5 mm ² cable cross-section
RS 422 (Fronius Solar Net)	RJ 45
Ethernet LAN	RJ 45, 100 MBit
Wi-Fi*	via USB Wi-Fi stick*

*optional


EASY INSTALLATION

- / No installation software needed
- / Patented direct connection between Fronius Datalogger and PC
- / Integral Fronius Signal Card function
- / Integral USB port to connect an optional Wi-Fi* stick

EASY CONFIGURATION

- / No firewall settings required for DSL connection
- / Easy configuration of service messages via e-mail, text message or fax
- / Wi-Fi* stick configured using the Fronius Datalogger Web website.

SIMPLE VISUALIZATION



1. FRONIUS DATALOGGER WEB WEBSITE: VIA ETHERNET OR WI-FI*.

/ The Fronius Datalogger Web has its own website to allow several users in a local network to view information quickly and easily.

Requirements: Web browser (e.g. Microsoft Internet Explorer 6.0, Firefox 2 or equivalent), PC/laptop on the same network as the Fronius Datalogger Web (e.g. via Wi-Fi*)

2. FRONIUS SOLAR.ACCESS: VIA ETHERNET OR WI-FI*.

/ The free Fronius Solar.access software is an advanced program for data evaluation and archiving on a local PC. As an administrator tool, it offers a full range of set-up options for all system components in Fronius Solar Net.

Requirements: Windows 2000/XP/Vista operating system, Microsoft Internet Explorer 6.0, Fronius Solar.access software (full version supplied), PC/laptop on the same network as the Datalogger Web (e.g. via Wi-Fi*), Fronius Solar.access installed on PV system.

3. FRONIUS SOLAR.WEB: VIA ETHERNET OR WI-FI*.

/ All data can be sent automatically to the Fronius Solar.web internet platform if required. This means both real-time data and archive data can be opened and viewed at any time on the internet.

Requirements: Active internet connection, web browser (e.g. Microsoft Internet Explorer 6.0, Firefox 2 or equivalent), PV system registered in Fronius Solar.web.

ACCESSORIES FOR THE FRONIUS DATALOGGER WEB: WI-FI* STICKS



/ For integrating the Fronius Datalogger Web into existing networks. The Wi-Fi* stick is configured using the Fronius Datalogger Web website. Wi-Fi* sticks are available for indoor and outdoor use.

/ Perfect Welding / Solar Energy / Perfect Charging

WE HAVE THREE DIVISIONS AND ONE PASSION: SHIFTING THE LIMITS OF POSSIBILITY.

/ Whether welding technology, photovoltaics or battery charging technology – our goal is clearly defined: to be the innovation leader. With around 3,000 employees worldwide, we shift the limits of what's possible - our more than 850 active patents are testimony to this. While others progress step by step, we innovate in leaps and bounds. Just as we've always done. The responsible use of our resources forms the basis of our corporate policy.

Further information about all Fronius products and our global sales partners and representatives can be found at www.fronius.com



v02 Feb 2014 EN



Fronius USA
 6797 Fronius Drive
 Portage, IN 46368
 USA
pv-support-usa@fronius.com
www.fronius-usa.com

Text and images correspond to the current state of technology at the time of printing. Subject to modifications. All information is without guarantee in spite of careful editing. Liability excluded. Copyright © 2011 Fronius™. All rights reserved.