

# blueplanet 125 TL3

Transformerless, three-phase string inverter.



## The trendsetter among inverters.

Optimized for solar power plants  
with 1500 volt modules

Extensive grid management  
functions

Special properties for extreme  
climatic conditions

Farsighted technical features for  
future requirements

Lean commissioning and  
maintenance via remote services

## Technical Data

<b>DC input data</b>		<b>125 TL3</b>
Max. recommended PV generator power		187 500 W
MPP range		875 – 1 300 V
Operating range		875 – 1 450 V
Rated DC voltage / start voltage		900 V / 1 000 V
Max. no-load voltage		1 500 V
Max. input current		160 A
Max. short circuit current $I_{sc\ max}$		300 A
Number of MPP tracker		1
Connection per tracker		1 - 2
<b>AC output data</b>		
Rated output		125 000 VA
Max. power		137 500 VA
Line voltage		600 V (3P+PE)
Voltage range (Ph-Ph)		480 – 760 V
Rated frequency (range)		50 Hz / 60 Hz (45 – 65 Hz)
Rated current		3 x 120.3 A
Max. current		3 x 132.3 A
Reactive power / cos phi		0 – 100 % Snom / 0.3 ind. – 0.30 cap.
Max. total harmonic distortion (THD)		≤ 3 %
Number of grid phases		3
<b>General data</b>		
Max. efficiency		99.2 %
Europ. efficiency		99.0 %
CEC efficiency		98.9 %
Standby consumption		6 W
Circuitry topology		transformerless
<b>Mechanical data</b>		
Display		LEDs
Control units		webserver, supports mobile devices
Interfaces		Ethernet (Modbus TCP, Sunspec) RS485 (KACO-protocol) USB, optional: 4-DI, WIFI
Fault signalling relay		potential-free NOC max. 30 V / 1 A
DC connection		cable lug, max. 240 mm <sup>2</sup> (0.372 in <sup>2</sup> ) Cu or Al
AC connection		cable lug, max. 240 mm <sup>2</sup> (0.372 in <sup>2</sup> ) Cu or Al
Ambient temperature		-25 °C – +60 °C <sup>1)</sup>
Humidity		0 – 100 %
Max. installation elevation (above MSL)		3 000 m
Min. distance from coast		500 m
Cooling		temperature controlled fan
Protection class		IP66 / NEMA 4X
Noise emission		59.2 db (A)
H x W x D		719 x 699 x 460 mm
Weight		78.2 kg
<b>Certifications</b>		
Safety		UL62109-1, UL1741, CSA-C22.2 No. 62109-1, CSA-C22.2 No. 62109-2, CSA-C22.2 No. 107.1 IEC 62109-1/-2, EN 61000-6-1/-2/-3, EN 61000-3-11/-12
Grid connection rule		overview see homepage / download area

<sup>1)</sup> Power derating at high ambient temperatures



Versions	S	XL
Number of DC inputs	1 - 2	1 - 2
DC switch	-	✓
DC SPD	Type 1 + 2	Type 1 + 2
AC SPD	○	○
RS485 interface SPD	○	○
Ethernet interface SPD	○	○
PID Set	○	○

standard = ✓ upgradeable = ○